

AD-752 439

THE INERTIAL WAVE FREQUENCY SPECTRUM IN
A CYLINDRICALLY CONFINED, INVISCID,
INCOMPRESSIBLE TWO COMPONENT LIQUID

Wayman E. Scott

Ballistic Research Laboratories

Prepared for:

Army Materiel Command

September 1972

DISTRIBUTED BY:

NTIS

National Technical Information Service
U. S. DEPARTMENT OF COMMERCE
5285 Port Royal Road, Springfield Va. 22151

AD 752439

BRL R 1609

BRL

AD

REPORT NO. 1609

THE INERTIAL WAVE FREQUENCY SPECTRUM IN A
CYLINDRICALLY CONFINED, INVISCID, INCOMPRESSIBLE,
TWO COMPONENT LIQUID

by

Wayman E. Scott

September 1972

Approved for public release; distribution unlimited.

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
U.S. Department of Commerce
Springfield, VA 22151

BALLISTIC RESEARCH LABORATORIES
ABERDEEN PROVING GROUND, MARYLAND

DDC
REFILED
DEC 14 1972
E

V3

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating or
sponsoring activity is prohibited.

Additional copies of this report may be purchased from
the U.S. Department of Commerce, National Technical
Information Service, Springfield, Virginia 22151

FORM 107	
DATE	FORM 107
DC	FORM 107
CLASSIFICATION	
DISTRIBUTION/AVAILABILITY CODES	
DISC.	AVAIL. CODE/REF. SYMBOL
A	

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute endorsement of any commercial product.*

BALLISTIC RESEARCH LABORATORIES

REPORT NO. 1609

SEPTEMBER 1972

THE INERTIAL WAVE FREQUENCY SPECTRUM IN A CYLINDRICALLY CONFINED,
INVISCID, INCOMPRESSIBLE, TWO COMPONENT LIQUID

Wayman E. Scott

Exterior Ballistics Laboratory

Approved for public release; distribution unlimited.

RD&E Project No. 1T061102A833D

ABERDEEN PROVING GROUND, MARYLAND

I-C

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) U. S. Army Ballistic Research Laboratories Aberdeen Proving Ground, Maryland 21005		2a. REPORT SECURITY CLASSIFICATION Unclassified	
		2b. GROUP	
3. REPORT TITLE THE INERTIAL WAVE FREQUENCY SPECTRUM IN A CYLINDRICALLY CONFINED, INVISCID, INCOMPRESSIBLE, TWO COMPONENT LIQUID			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (First name, middle initial, last name) WAYMAN E. SCOTT			
6. REPORT DATE September 1972		7a. TOTAL NO. OF PAGES 222	7b. NO. OF REFS 6
8a. CONTRACT OR GRANT NO.		8b. ORIGINATOR'S REPORT NUMBER(S) BRL Report No. 1609	
a. PROJECT NO. RDT&E 1T061102A8J3D			
c.		8b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.			
10. DISTRIBUTION STATEMENT Approved for public release; distribution unlimited.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY U. S. Army Materiel Command Washington, D. C. 20315	
13. ABSTRACT A theoretical and experimental study is made of the phenomenon indicated in the title. It is shown that for inertial waves, just as for gravity waves, there are discontinuities in the tangential particle velocities at the interface in a real, two-component liquid, a fact implying the existence of a vortex sheet. For the case where the two liquids completely fill the cylinder, other results are obtained that are analogous to those for gravity waves. In particular, if the liquids are nearly of the same density, there are two sets of frequencies, one set characterizing oscillations of the liquid mass as a whole, the other set characterizing very low frequency oscillations at the interface. For the case in which the two liquids have markedly different densities, there are again two sets of frequencies, one set characterizing oscillations of the inner liquid as though the outer liquid were a solid mass, the other set characterizing oscillations of the outer liquid as though the inner liquid were absent. For the general case, physical interpretations are difficult; hence, a table of frequencies versus composition is given.			

T-A

DD FORM 1473

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS OBSOLETE FOR ARMY USE.

UNCLASSIFIED

Security Classification

UNCLASSIFIED
Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
FLUID DYNAMICS PHYSICS MATHEMATICS						
I-B						

UNCLASSIFIED
Security Classification

BALLISTIC RESEARCH LABORATORIES

REPORT NO. 1609

WEScott/ds
Aberdeen Proving Ground, Md.
September 1972

THE INERTIAL WAVE FREQUENCY SPECTRUM IN A CYLINDRICALLY CONFINED,
INVISCID, INCOMPRESSIBLE, TWO COMPONENT LIQUID

ABSTRACT

A theoretical and experimental study is made of the phenomenon indicated in the title. It is shown that for inertial waves, just as for gravity waves, there are discontinuities in the tangential particle velocities at the interface in a real, two-component liquid, a fact implying the existence of a vortex sheet. For the case where the two liquids completely fill the cylinder, other results are obtained that are analogous to those for gravity waves. In particular, if the liquids are nearly of the same density, there are two sets of frequencies, one set characterizing oscillations of the liquid mass as a whole, the other set characterizing very low frequency oscillations at the interface. For the case in which the two liquids have markedly different densities, there are again two sets of frequencies, one set characterizing oscillations of the inner liquid as though the outer liquid were a solid mass, the other set characterizing oscillations of the outer liquid as though the inner liquid were absent. For the general case, physical interpretations are difficult; hence, a table of frequencies versus composition is given.

TABLE OF CONTENTS

	Page
ABSTRACT	3
LIST OF SYMBOLS.	7
I. INTRODUCTION	9
II. ANALYSIS	9
A. Mathematical	9
B. Experimental	19
ACKNOWLEDGMENT	20
REFERENCES	21
DISTRIBUTION LIST.	22

LIST OF SYMBOLS

a	inner radius of free surface
b	radius of surface separating the two liquids
c	outer radius of cavity
d	one-half cylinder height
i	$\sqrt{-1}$
J	Bessel function of first kind
K_1	$\Omega^2 a / S^2 [1 + (2\Omega/S)^2]$
K_2	$2\Omega i / S$
K_3	$((2j + 1) \pi i / 2d) / \sqrt{1 + (2\Omega/S)^2}$
p	pressure
r, θ , z	cylindrical coordinates
S	frequency
t	time
<u>u</u>	perturbation velocity
Y	Bessel function of second kind
ρ	density
Ω	angular speed of liquid

I. INTRODUCTION

Lamb^{1*} notes some interesting facts about gravity wave motion in inviscid, incompressible, superposed liquids of different densities, e.g., the diminution of the speed of a wave from the value it would have in a one-component liquid, the long natural period of oscillation of the interface of two liquids of nearly equal density, the mathematically possible but experimentally unobserved "breaking" of the waves at the interface, the independent oscillations of the two liquids if the densities are markedly different, and the presence of a vortex sheet at the interface. This note investigates mathematically and experimentally whether that class of internal waves now commonly termed inertial waves (Bjerkness², and Fultz³) exhibit such phenomena when confined in a right circular cylinder.

II. ANALYSIS

A. Mathematical

1. The Governing Equations. Consider Figure 1. Following Stewartson³, we initially assume that the inviscid, incompressible liquids are spinning uniformly as a rigid body, that $\Omega^2 b^2$ and $\Omega^2 c^2$ are much greater than dg , and that $\rho_2 > \rho_1$. Then in this steady state, we have:

$$0 = -\nabla \left[\frac{P_{10}}{\rho_1} - \frac{\Omega^2}{2} (r^2 - a^2) \right], \quad a < r < b \quad (1)$$

and

$$0 = -\nabla \left[\frac{P_{20}}{\rho_2} - \frac{\rho_1}{\rho_2} \frac{\Omega^2}{2} (b^2 - a^2) - \frac{\Omega^2}{2} (r^2 - b^2) \right], \quad b < r < c \quad (2)$$

where P_{10} and P_{20} are the "static" pressures in the uniformly spinning liquids, and where the coordinate system has the angular velocity $\underline{\Omega} = (0, 0, \Omega)$.

*References are listed on page 21.




Figure 1. Definition of Coordinate System

After a momentary disturbance of the container that generates a "perturbation" velocity $\underline{u} = (u, v, w)$, the linearized Euler equations in the two regions are:

$$\frac{\partial}{\partial t} \underline{u}_1 + 2\Omega \times \underline{u}_1 = - \nabla \left[\frac{P_1}{\rho_1} - \frac{\Omega^2}{2} (r^2 - a^2) \right] \quad (3)$$

and

$$\frac{\partial}{\partial t} \underline{u}_2 + 2\Omega \times \underline{u}_2 = - \nabla \left[\frac{P_2}{\rho_2} - \frac{\rho_1}{\rho_2} \frac{\Omega^2}{2} (b^2 - a^2) - \frac{\Omega^2}{2} (r^2 - b^2) \right] \quad (4)$$

where P_1 , \underline{u}_1 and P_2 , \underline{u}_2 are the two pressures and perturbation velocities in the two regions after the disturbance. Subtracting (1) from (3) and (2) from (4), we have

$$\frac{\partial}{\partial t} \underline{u}_k + 2\Omega \times \underline{u}_k = - \nabla \left(\frac{P_k - P_{k0}}{\rho_k} \right) \equiv - \nabla \frac{P'_k}{\rho_k}, \quad k = 1, 2 \quad (5)$$

where P'_1 and P'_2 may properly be termed perturbation pressures.

Again following Stewartson⁴, we seek normal mode solutions of equation (5). Hence, letting all time-dependent terms have the same functional e^{st} dependence, one gets (Miles⁵, 1959):

$$\underline{u}_k = \left[\frac{2\Omega}{S} \times - 1 - \frac{2\Omega}{S} \frac{2\Omega}{S} \cdot \right] \frac{\nabla P'_k}{S\rho_k [1 + (2\Omega/S)^2]} \quad (6)$$

From the continuity equation $\nabla \cdot \underline{u}_k = 0$, one gets:

$$\nabla^2 P'_k + \left(\frac{2\Omega}{S} \cdot \nabla \right)^2 P'_k = 0 \quad (7)$$

We solve equation (7) by the usual separation of variables process, getting:

$$P'_k(r, \theta, z) = \sum_{m_k=1} e^{im_k \theta} \left[A_k J_{m_k} \left(\frac{\lambda_k}{d} r \sqrt{1 + \left(\frac{2\Omega}{S} \right)^2} \right) + B_k Y_{m_k} \left(\frac{\lambda_k}{d} r \sqrt{1 + \left(\frac{2\Omega}{S} \right)^2} \right) \right] \cdot \left[C_k \cos h \frac{\lambda_k}{d} z + D_k \sin h \frac{\lambda_k}{d} z \right] \quad (8)$$

where the J's and Y's are Bessel functions of the first and second kinds, respectively, where the λ 's and m 's are separation constants, and where A_k, B_k, C_k, D_k are integration constants.

2. The Frequency Equation. After the disturbance, the container has only the angular velocity $(0, 0, \Omega)$; hence, the boundary condition on all solid surfaces is $\underline{u} \cdot \underline{n} = 0$, where \underline{n} is an outward directed unit normal. On the end face, then, we have:

$$\left[\frac{\partial P'_k}{\partial z} \right]_{z = \pm d} = 0 \quad (9)$$

from which there follows $C_k = 0$, and

$$\lambda_1 = \lambda_2 = (2j + 1) \frac{\pi i}{2}, \quad i = \sqrt{-1}, \quad j = 0, 1, 2, \dots \quad (10)$$

Hence, redefining our constants, we rewrite (8) as:

$$P'_k = \sum_{j=0} \sum_{m_k=1} e^{im_k \theta} \left[A'_k J_{m_k} (K_3 r) + B'_k Y_{m_k} (K_3 r) \right] \sin (2j + 1) \frac{\pi z}{2d} \quad (11)$$

where

$$K_3 = (2j + 1) \frac{\pi i}{2d} \sqrt{1 + \left(\frac{2\Omega}{S} \right)^2} \quad (12)$$

On the lateral surface $r = c$, the condition $\underline{u} \cdot \underline{n} = 0$ gives:

$$\begin{aligned}
\left[\frac{\partial P'_2}{\partial r} + \frac{2\Omega}{Sr} \frac{\partial P'_2}{\partial \theta} \right]_{r=c} &= 0 \\
&= A'_2 \left[K_3 J'_{m_2} (K_3 c) + K_2 \frac{m_2}{c} J_{m_2} (K_3 c) \right] \\
&\quad + B'_2 \left[K_3 Y'_{m_2} (K_3 c) + K_2 \frac{m_2}{c} Y_{m_2} (K_3 c) \right] \quad (13)
\end{aligned}$$

where

$$K_2 \equiv \frac{2\Omega i}{S} \quad (14)$$

In section B we outline how we search for the liquid eigenfrequencies experimentally by adjusting certain physical parameters until the gyroscope undamps. Inferring that this undamping is due to resonance between one of the liquid eigenfrequencies and the nutational frequency of the gyroscope (see Stewartson⁴, 1957), one can determine that particular eigenfrequency. Though the validity of this procedure is well documented, it nevertheless affords a determination of only those modes for which $m_2 = 1$, for one can show that coupling between the liquid and shell motions occurs only for that value of m_2 . Hence, the form of equation (13) pertinent for this study is:

$$\begin{aligned}
&A'_2 \left[K_3 J'_1 (K_3 c) + \frac{K_2}{c} J_1 (K_3 c) \right] \\
&+ B'_2 \left[K_3 Y'_1 (K_3 c) + \frac{K_2}{c} Y_1 (K_3 c) \right] = 0 \quad (15)
\end{aligned}$$

On the inner free surface (at $r = a$), the kinematical boundary condition is $\frac{DF}{Dt} = 0$, where $F \equiv r - a - \eta(\theta, z, t) = 0$, and $\eta(\theta, z, t)$ is the free surface elevation. Hence, to first order, the kinematical boundary condition is

$$\left[u_1 - \frac{\partial \eta}{\partial t} \right]_{r=a+\eta} = 0 = \left[u_1 - S\eta \right]_{r=a+\eta} \quad (16)$$

The dynamic boundary condition on the inner free surface is $P_1 = 0$.

In terms of P'_1 , this is:

$$P'_1 \Big|_{r=a+\eta} = - P_{10} \Big|_{r=a+\eta} \dot{=} - \rho_1 \Omega^2 a \eta. \quad \text{Hence:}$$

$$SP'_1 + \rho_1 \Omega^2 a u_1 \Big|_{r=a+\eta} = 0 \quad (17)$$

which, in terms of (11), is:

$$\begin{aligned} & A'_1 \left[J_{m_1}(K_3 a) - K_1 \left\{ K_3 J'_{m_1}(K_3 a) + K_2 \frac{m}{a} J_{m_1}(K_3 a) \right\} \right] \\ & + B'_1 \left[Y_{m_1}(K_3 a) - K_1 \left\{ K_3 Y'_{m_1}(K_3 a) + K_2 \frac{m}{a} Y_{m_1}(K_3 a) \right\} \right] = 0 \quad (18) \end{aligned}$$

where

$$K_1 \equiv \frac{\Omega^2 a}{S^2 \left[1 + \left(\frac{2\Omega}{S} \right)^2 \right]} \quad (19)$$

At the interface $r = b$, continuity of the pressure and normal velocity yield two dynamic boundary conditions⁶. From the continuity of the normal velocity we have:

$$u_1 \Big|_{r=b+\eta} = u_2 \Big|_{r=b+\eta}, \quad \text{or:}$$

$$\begin{aligned}
& \sum_{m_1=1}^{\infty} \frac{e^{im_1\theta}}{\rho_1} \left[K_3 \left\{ A'_1 J'_{m_1}(K_3 b) + B'_1 Y'_{m_1}(K_3 b) \right\} \right. \\
& \quad \left. + K_2 \frac{1}{b} \left\{ A'_1 J'_{m_1}(K_3 b) + B'_1 Y'_{m_1}(K_3 b) \right\} \right] \\
& = \frac{e^{i\theta}}{\rho_2} \left[K_3 \left\{ A'_2 J'_1(K_3 b) + B'_2 Y'_1(K_3 b) \right\} \right. \\
& \quad \left. + K_2 \frac{1}{b} \left\{ A'_2 J'_1(K_3 b) + B'_2 Y'_1(K_3 b) \right\} \right] \quad (20)
\end{aligned}$$

Hence, $m_1 = 1$.

From the equality of pressures at the interface, we have $(P_1)_{r=b+\eta} = (P_2)_{r=b+\eta}$, or $(P'_1 + P_{10})_{r=b+\eta} = (P'_2 + P_{20})_{r=b+\eta}$. Hence, to first order in η , we have: $(P'_1 - P'_2)_{r=b+\eta} = b \eta^2 (\rho_2 - \rho_1)$, from which there follows: $[SP'_1 + \rho_1 \Omega^2 b u_1]_{r=b+\eta} = [SP'_2 + \rho_2 \Omega^2 b u_2]_{r=b+\eta}$. Substituting for P'_1 , P'_2 , u_1 , and u_2 , we have:

$$\begin{aligned}
& A'_1 \left[J_1(K_3 b) - K_1 \frac{b}{a} \left\{ K_3 J'_1(K_3 b) + \frac{K_2}{b} J_1(K_3 b) \right\} \right] \\
& + B'_1 \left[Y_1(K_3 b) - K_1 \frac{b}{a} \left\{ K_3 Y'_1(K_3 b) + \frac{K_2}{b} Y_1(K_3 b) \right\} \right] \\
& = A'_2 \left[J_1(K_3 b) - K_1 \frac{b}{a} \left\{ K_3 J'_1(K_3 b) + \frac{K_2}{b} J_1(K_3 b) \right\} \right] \\
& + B'_2 \left[Y_1(K_3 b) - K_1 \frac{b}{a} \left\{ K_3 Y'_1(K_3 b) + \frac{K_2}{b} Y_1(K_3 b) \right\} \right] \quad (21)
\end{aligned}$$

Equations (15), (18), (20), and (21) are a set of four homogeneous equations for the determination of A'_1 , B'_1 , A'_2 , and B'_2 . For convenience, we re-write these four equations in the form

$$A'_1 \cdot 0 + B'_1 \cdot 0 + A'_2 \ell_{23}(c) + B'_2 \ell_{24}(c) = 0 \quad (22)$$

$$A'_1 \ell_{11}(a) + B'_1 \ell_{12}(a) + A'_2 \cdot 0 + B'_2 \cdot 0 = 0 \quad (23)$$

$$A'_1 \rho_{123} \ell_{123}(b) + B'_1 \rho_{124} \ell_{124}(b) - A'_2 \rho_{213} \ell_{213}(b) - B'_2 \rho_{214} \ell_{214}(b) = 0 \quad (24)$$

$$A'_1 \ell_{11}(b) + B'_1 \ell_{12}(b) - A'_2 \ell_{21}(b) - B'_2 \ell_{22}(b) = 0 \quad (25)$$

where the definitions of the several ℓ 's are obvious.

From the above set of equations one can express P'_1 and P'_2 in terms of A'_1 . Then, from $v_1 = \underline{u}_1 \cdot \underline{i}_\theta = \frac{1}{\rho_1 S \left[1 + \left(\frac{2\Omega}{S} \right)^2 \right]} \left[\frac{2\Omega}{S} \frac{\partial P'_1}{\partial r} - \frac{1}{r} \frac{\partial P'_1}{\partial \theta} \right]$ and

$$v_2 = \underline{u}_2 \cdot \underline{i}_\theta = \frac{1}{\rho_2 S \left[1 + \left(\frac{2\Omega}{S} \right)^2 \right]} \left[\frac{2\Omega}{S} \frac{\partial P'_2}{\partial r} - \frac{1}{r} \frac{\partial P'_2}{\partial \theta} \right], \text{ one can show that}$$

$$v_1 \Big|_{r=b} \neq v_2 \Big|_{r=b}. \text{ Hence, as is the case for gravity waves in superposed}$$

liquids¹, one infers that for inertial waves in a real liquid there would be a vortex sheet at the interface.

Equations (22) - (25) are a homogeneous set, and a necessary condition that A'_1 , B'_1 , A'_2 , and B'_2 be non-zero is that the determinant of the coefficients be zero. Hence:

$$\begin{vmatrix} 0 & 0 & \ell_3(c) & \ell_4(c) \\ \ell_1(a) & \ell_2(a) & 0 & 0 \\ \rho_2 \ell_3(b) & \rho_2 \ell_4(b) & -\rho_1 \ell_3(b) & -\rho_1 \ell_4(b) \\ \ell_1(b) & \ell_2(b) & -\ell_1(b) & -\ell_2(b) \end{vmatrix} = 0 \quad (26)$$

which is the frequency equation.

We first consider a special case of (26). Let the two liquids completely fill the cylinder. Then $a = 0$ and equation (26) reduces to

$$\begin{vmatrix} 0 & \ell_3(c) & \ell_4(c) \\ \rho_2 \ell_3(b) & -\rho_1 \ell_3(b) & -\rho_1 \ell_4(b) \\ \ell_1(b) & -\ell_1(b) & -\ell_2(b) \end{vmatrix} = 0 = -(\rho_2 - \rho_1) \ell_1(b) \ell_3(b) \ell_4(c) - \ell_3(c) [\rho_1 \ell_1(b) \ell_4(b) - \rho_2 \ell_3(b) \ell_2(b)] \quad (27)$$

We now consider two special cases of equation (27).

Case I: $\rho_2 \neq \rho_1$

Then, from (27), we have:

$$\ell_3(c) \equiv K_3 J_1'(K_3 c) + \frac{K}{c} J_1(K_3 c) = 0 \quad (28)$$

which is Stewartson's inertial wave frequency equation for a one-component liquid completely filling a cylinder of radius c .

Alternatively, from (27) we have:

$$\begin{aligned} \ell_4(b) \ell_1(b) - \ell_3(b) \ell_2(b) &\equiv J_1(K_3 b) \left[K_3 Y_1'(K_3 b) + \frac{K}{b} Y_1(K_3 b) \right] \\ &- Y_1(K_3 b) \left[K_3 J_1'(K_3 b) + \frac{K}{b} J_1(K_3 b) \right] = 0 \end{aligned} \quad (29)$$

Using the asymptotic expansions for the Bessel functions, one can show that (29) is satisfied if K_3 is very large. However, a large K_3

implies a small β , a result establishing the existence of low frequency waves at the interface.

Hence, we've shown that, if $\rho_1 \approx \rho_2$, there are two sets of inertial wave frequencies, one set for the liquid as a whole, the other for the oscillations at the interface. A similar result holds for gravity waves.

Case II: $\rho_2 \gg \rho_1$

Then, from (27), we have:

$$\ell_3(b) \equiv K_3 J_1'(K_3 b) + \frac{K}{b} J_1(K_3 b) = 0 \quad (30)$$

This would be the Stewartson frequency equation for the inner liquid if the outer liquid were a solid mass.

Alternatively, from (27), we have:

$$\begin{aligned} \ell_1(b)\ell_4(c) - \ell_3(c)\ell_2(b) &= 0 \\ &= \left[J_1(K_3 b) - K_1(b) \left\{ K_3 J_1'(K_3 b) + \frac{K}{b} J_1(K_3 b) \right\} \right] \left[K_3 Y_1'(K_3 c) + \frac{K}{c} Y_1(K_3 c) \right] \\ &\quad - \left[K_3 J_1'(K_3 c) + \frac{K}{c} J_1(K_3 c) \right] \left[Y_1(K_3 b) - K_1(b) \left\{ K_3 Y_1'(K_3 b) + \frac{K}{b} Y_1(K_3 b) \right\} \right] \end{aligned} \quad (31)$$

This is the Stewartson frequency equation for a one component liquid, with a free surface at $r = b$, in a cylinder of radius c .

Hence, we've established that, if $\rho_2 \gg \rho_1$, there are also two sets of inertial wave frequencies, one characterizing the inner liquid as though the outer were solid; the other characterizing the outer liquid as though the inner were absent. A similar result holds for gravity waves.

For the general case, where $a \neq 0$, and ρ_1 and ρ_2 are neither nearly equal nor far removed, equation (26) does not easily lend itself to such

physical interpretations. Hence, we merely give a table of theoretically and experimentally determined frequencies versus composition for a particular density ratio*.

Table I.

$\frac{\rho_1}{\rho_2}$	$\frac{c}{d}$	$\frac{b}{d}$	$\frac{a}{d}$	$\frac{S}{i\Omega}$ (Theory)	$\frac{S}{i\Omega}$ (Experimental)
.8	3.127	2.708	0	- .931	- .936
.8	3.127	2.211	0	- .927	- .934
.8	3.127	1.564	0	- .938	- .942
.8	3.127	2.752	.989	- .926	- .924
.8	3.127	2.319	.989	- .914	- .920
.8	3.127	1.783	.989	- .931	- .926

B. Experimental

Two immiscible liquids are placed in a cylindrical cavity inside a gyroscope. Details of the gyroscope, supporting apparatus, and the experimental procedure for determining the liquid eigenfrequencies by resonating one of them with the nutational frequency of the gyroscope, are profusely documented elsewhere⁴. We merely note here that the inertial waves can create an asymmetrical pressure distribution in the cavity; and the above-mentioned state of resonance merely ensures that the asymmetrical pressure distribution will "keep step" with the nutational motion, thus causing an overturning effect that results in a growth of the nutational component of the motion of the gyroscope. Since the effect involves integrals like

$$\int_0^{2\pi} e^{im\theta} (\cos \theta, \sin \theta) d\theta$$

that are zero unless $m = 1$, only those modes of oscillation for which

*See Section B.

$m = 1$ couple with the shell motion. Hence, it is only such modes that we can find with the gyroscope.

Since viscosity undoubtedly has an effect, it was essential that the two liquids of different density have small, equal, kinematic viscosities. Fortunately, the Dow-Corning Company has just developed a light oil that has a kinematic viscosity (one centistoke) equal to that of water, yet with a specific gravity of 0.8. All of the experiments were run using water and this oil, and the results are given in Table I.

ACKNOWLEDGMENT

The author is grateful to Mr. William Mermagen who suggested the study.

REFERENCES

1. H. Lamb, *Hydrodynamics*, Dover Publications, New York, 1945.
2. V. Bjerkness, et al, *Physikalische Hydrodynamik*, Verlag von Julius Springer, Berlin, 1933, Vol. I, pp. 177-181.
3. D. Fultz, "A Note on the Over-Stability and the Elastoid-Inertia Oscillations of Kelvin, Bjerkness, et al," *Journal of Meteorology* 16, 1959, pp. 199-208.
4. K. Stewartson, "On the Stability of a Spinning Top Containing a Liquid," *Journal of Fluid Mechanics*, 5, 1959, pp. 577-592.
5. J. W. Miles, "Free Surface Oscillations in a Slowly Rotating Liquid," *Physics of Fluids*, 12, p. 298, (1959)
6. G. K. Batchelor, *Fluid Dynamics*, Cambridge, at the University Press, London, 1967.